

INDUSTRIAL PUSH-IN - Fittings

NORGREN

PLASTIC - METRIC

This range of plastic push-in fittings provide a secure joint without the use of any tools making them quick and easy to fit. They can be used on nylon, plastic, calibrated copper or Bundy Tubes to carry air, water and many other liquids, except acids **but not suitable for fuel**. We recommend the use of tube supports with nylon or plastic tubing.

We do not advise the use of plastic push-in fittings on vehicle brake lines.

Maximum working pressure 18 bar. Minimum burst pressure 25 bar. Temp: -20 to +70°C



STRAIGHT CONNECTOR

Tube OD	Single	
	Part No	Pkt Part No
4mm	4410	PIF001
5mm	4411	PIF002
6mm	4412	PIF003
8mm	4413	PIF004
10mm	4415	PIF006
12mm	4416	PIF008
16mm	4419	



TEE CONNECTOR

Tube OD	Single	
	Part No	Pkt Part No
4mm	4451	PIF021
5mm	4452	PIF022
6mm	4453	PIF023
8mm	4454	PIF024
10mm	4455	PIF026
12mm	4456	PIF028
16mm	4458	PIF030



ELBOW CONNECTOR

Tube OD	Single	
	Part No	Pkt Part No
4mm	4471	PIF011
6mm	4473	PIF013
8mm	4474	PIF014
10mm	4475	PIF016
12mm	4476	PIF018
16mm	4478	

STRAIGHT STUD




Thread BSPT	Tube OD	Single	
		Part No	Pkt Part No
1/8	4mm	4441	PIF031
1/8	6mm	4442	
1/8	8mm	4449	
1/4	6mm	4443	PIF033
1/4	8mm	4450	PIF034
1/4	10mm	4444	PIF036
3/8	10mm	4445	PIF037
3/8	12mm	4447	PIF039
1/2	10mm	4446	PIF041
1/2	12mm	4448	

SWIVEL ELBOW



Thread BSPT	Tube OD	Single
		Part No
1/8	4mm	4461
1/8	6mm	4462
1/4	6mm	4463
1/8	8mm	4469
1/4	8mm	4470
1/4	10mm	4464
3/8	10mm	4465
3/8	12mm	4467
1/2	10mm	4466
1/2	12mm	4468



Tube OD	Part No	Single
6mm	4481	Single
8mm	4482	Single

Y CONNECTOR

Phone: 01474 321954 Fax 01474 321988