

# Air Brake - Tubing

## AIR COILS UNICOILS

Amended 14.04.10



Black Coil conforming to DIN Standard 74323 with Colour Coded Ends for clear identification. These un coils have moulded anti-kink protection for longer life with a 20 coil 4 metre working length. The universal end fittings create no replacement olive problems and adaptors are available for all applications. They have a stowage loop for safety when uncoupled.

20 TURN COILS	
Part No	Description
2027	Unicoil 20 Turn <b>Yellow</b> Tail
2028	Unicoil 20 Turn <b>Red</b> Tail
2017	Unicoil 22 Turn <b>Yellow</b> Tail
2018	Unicoil 22 Turn <b>Red</b> Tail

22 TURN COIL	
Part No	Description
9018	M18 (Female) x 3/8 (Male) Ends - Black <b>Yellow</b> Tail
9019	M18 (Female) x 3/8 (Male) Ends - Black <b>Red</b> Tail

MALE ENDS	
Part No	Description
2019	M18 - 1/4NPT Coil End Adaptor
2021	M18 Male - 1/2 BSP Male End
2022	M18 Male - M22 Male End
2023	M18 Male - M16 Male End
2024	M18 Male - M18 Male (34mm long) End
2025	M18 Male - M16 Male (34mm long) End
2026	Assorted Box of End Fittings

**Phone: 01474 321954 Fax 01474 321988**

# Air Brake - Tubing

## AIR COILS Unicoil Kit

Amended 14.04.10

Part No 2020

### Contents

**5 x Yellow Coils - Part No 2027**

**5 Red Coils - Part No 2028**

**1 x Assorted Box Ends - Part No 2026**

Application List			
Model	Part No	Pkt Part No	Quantity per Coil
Scania/Iveco	2023	UNI 001	1
	2025		1
Renault/Volvo	2023	UNI 002	2
MAN	2024	UNI 003	1
	2025		1
DAF/MERCEDES	2023		2
1/2 BSP Application	2021	UNI 004	2
M22 Application	2022	UNI 005	2
M16 Application	2023	UNI 006	2

## COMPACT ANTI-KINKING COILS



**Part No 2127**



**Part No 2128**

As well as the security of these coils being manufactured by one of the largest suppliers to most OE truck manufacturers, these have been designed with the UK fleet specifically in mind. Many of the larger UK supermarket fleets are now specifying these coils to be supplied above all others due to their excellent long term performance and cost benefits.

These coils have a 40mm ID coil diameter with a 4m working length. They meet DIN standards 74323 and 74324 with a burst pressure that exceeds 57 bar at 23°C and a safety factor of 3 at 70°C. These coils have the strength of Polyamide with the flexibility of Polyurethane and are benchmarked as best in their class.

**Phone: 01474 321954 Fax 01474 321988**

# Air Brake - Tubing

## AIR COILS Amended 14.04.10

### Air Coil Handles

#### Part No 2029

contains

1 x **Red** Handle

1 x **Yellow** Handle

2 x M16 F/M M16 Male Bulkhead Adaptor



These handles are ergonomically designed to assist with grip when connecting and disconnecting Air Coils especially in poor conditions.

#### Additional Options

Part No	Description
2023	Standard Air Coil Conversion = M18 Male to M16 Male-Use
7604	M22 C Couplings/Palm Couplings = M16 Female to M22 Male-Use
7607	1/2 BSP C Couplings/Palm Couplings = M16 Female to 1/2 BSP Male-Use

## TRUCK COILS

22 Turn Coils			
Type	Part No	Colour	Description
Volvo	2266	<b>Red</b>	M16 End x M16x1.5 End
Volvo	2267	<b>Yellow</b>	M16 End x M16x1.5 End
Scania	2269	<b>Red</b>	M18 34mm long Bulkhead with M16x1.5 Thread
Scania	2270	<b>Yellow</b>	M18 34mm long Bulkhead with M16x1.5 Thread

**Phone: 01474 321954 Fax 01474 321988**