

Industrial - Tubing

CLEAR BRAIDED PVC TUBING

This clear tubing is reinforced with polyester fibre braid and offers exceptional chemical and physical properties. It is flexible and lightweight as well as being resistant to most acids and alkalis. Supplied in 30 metre coils.

Amended 14.04.10



Tube ID	Part No	Max Work Pressure	O Clip	Wormdrive
3/16"	1913	20 bar	2004	2031
1/4"	1914	17 bar	2006	2031
5/16"	1915	13 bar	2007	2032
3/8"	1916	10 bar	2009	2032
1/2"	1917	9 bar	2010	2033
5/8"	1918	8 bar	2014	2035
3/4"	1919	7 bar	-	2036
1"	1920	5 bar	-	2038

CLEAR PVC TUBING

This exceptionally clear PVC tubing has a wide range of applications for low pressure work. It is resistant to oils, grease and solvents. Supplied in 30 metre coils.



Tube ID	Wall Thickness	Part No	O Clip	Worm-drive
1/8"	1/16"	1931	2002	-
3/16"	1/16"	1933	2003	-
1/4"	1/16"	1934	2004	-
5/16"	1/16"	1935	2006	2031
3/8"	1/16"	1936	2006	2031

Windscreen washer tube
4mm ID 6mm OD.

Part No. 1951

Tube ID	Wall Thickness	Part No	O Clip	Worm-drive
1/4"	1/8"	1944	2006	2031
5/16"	1/8"	1945	2007	2032
3/8"	1/8"	1946	2009	2032
1/2"	1/8"	1947	2010	2033
5/8"	1/8"	1948	2012	2035
1"	1/8"	1950	-	2036

Rigid Nylon Tubing

For use in air ring mains this blue unplasticised nylon 12 pipe is available in packs of 5 x 3 metre lengths

Size mm	Part No
15 x 12	1406
22 x 18	1408
28 x 23	1409



Pipe Clips & Spacer

Part No	Pkt 10
2727	15mm
2728	22mm
2729	28mm
2730	Spacer



Phone: 01474 321954 Fax 01474 321988